

RY-850

Paper Cup Printing Machine

LINTEK



Characteristics:

1. Adopt the anilox roller to spread ink.
2. Unwinding and rewinding are controlled by magnetic power brake, clutch, (or by automatic tension controller of Mitsubishi, made in Japan).
3. Each printing unit adopt 360o for registration.
4. Each printing unit have one IR drier.
5. The rubber roller can break away automatically while parking, and running at a low speed, in order to avoid ink being dry.
6. The main motor is adopted the import stepless regulation of frequency conversion.
7. Unwinding, web guiding, corona discharging ,

printing, IR drying and rewinding can be finished in one process, this is an ideal machine to print many kinds of paper cup.

Main Technical Parameters

Model	RY-650	RY-850
Printing Speed	60m/min	60m/min
Printing Color	1-6 Colors	1-6 Colors
Max. Web Width	660mm	860mm
Max. Printing Width	650mm	850mm
Max. Printing Diameter	1400mm	1400mm
Max. Winding Diameter	1400mm	1400mm
Printing Girth	180-420mm	180-420mm
Precision of Chromatography	±0.15mm	±0.15mm
Dimensions(L*W*H)	3500×1650×2200mm	3500×1850×2200mm
Machine Weight	About 3200kg	About 3800kg